VScom 400LRJ45 UPCI



4 RS232 Ports RJ45 UPCI Card

Hardware Specifications	
Ports	4 x RS232 (RxD, TxD, RTS, CTS, DTR, DSR, DCD, RI)
UART	4 x 16550 (16 Byte FIFO)
Address	Plug and Play
	PCI Plug and Play, only one interrupt/card
	max. 921 kbps
Bus Interface	Universal PCI 3.3V / 5.0V
Connectors	4 x RJ45
	L120mm x H89mm
Temperature	0°C - 55°C
Performance Features	
FIFO	FIFO size 16Byte
	adjustable Rx 1,4,8,14Bytes Tx 1 up to 16Bytes
Handshake	RTS / CTS, Xon / Xoff
Speed	1bps up to 921kbps, Multiplication factor for legacy applications,
UART	UART emulation of 8250 and 16450
Operating Systems	
	VScom high performance serial driver, x86 and x64 Editions
Server 2000 to 2008 R2	VScom high performance serial driver, x86 and x64 Editions
Windows NT 4.0	VScom high performance serial driver
	control panel applet
Windows 95, 98, SE, ME	VScom high performance serial driver
DOS	Virtuell address driver and compatibility tools
	Real DOS Com port emulation
OS/2	Supported by COM16 driver in recent system releases
	Third party serial driver SIO.SYS available
Linux	Kernel 2.6 and up: built-in support
	Previous kernel: VScom high performance real tty driver
div.UNIX	Configuration instructions
Approvals	
EMC	FCC Class A, CE Class A
Environment	RoHS
Ordering Information	
	4474
Product Name	VScom 400LRJ45 UPCI
Packing list	VScom 400LRJ45 UPCI Card
	CD, English documentation

Overview

The L-series is an economic solution for standard applications. The serial ports are based on a 16C550A UART with 16 byte FIFO. The eightfold maximum speed allows some irregular transmission rates.

©2013, VSCOM. The VSCOM logo is a trademark of VS Vision Systems GmbH. Other products and brand names mentioned herein may be trademarks or registered trademarks of their respective owners. The information contained herein is subject to change without notice.

You can purchase VSCOM's products easily from a wide variety of leading technology distributors or partners. Please contact us to find the best ordering method for your needs.

Connect to Success