

VScom USB-8COM-M CBL

USB to 8 RS232 Ports Adapter

Hardware Specifications	
Serial Interface	8 x RS232 Connector 1 x DB62 female, Adapters available Speed up to 500 kbps Signals TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND
USB Interface	USB 2.0 ▪ Bus powered ▪ No external power supply
Driver	Windows 2000 to Windows 8 (x86 and x64) Windows Server 2000 to 2008 R2 (x86 and x64) Linux (Kernel 2.6 built-in, 2.4 available)
Dimensions	123 x 75 x 30 mm ³ (W x D x H)
Approvals	
EMC	FCC Class A, CE Class A
Environment	RoHS
Ordering Information	
Art. No.	652
Product Name	VScom USB-8COM-M CBL
Packing list	♦ VScom USB-8COM-M CBL Adapter ♦ USB cable 0,9m
Optional Accessories	♦ DK 35A (Art No. 662) - DIN-Rail mounting kit ♦ DB62 to ... Octopus cables and connection box

Overview

Serial ports on USB allow further use of existing devices, even when the computer doesn't offer serial ports.

The high speed serial port with the 128 byte FIFO allow high speed communication, even in heavy loaded systems. Unique features reduce the system load. The serial port also allows unusual speed settings like 500.000bps.

USB-8COM-M CBL uses a small case due to the high-density DB62 combi connector for the serial ports. Mounted even in narrow environment, it connects to serial devices via an octopus cable or a connection box.

©2013, VSCOM. The VSCOM logo is a trademark of VS Vision Systems GmbH. Other products and brand names mentioned herein may be trademarks or registered trademarks of their respective owners. The information contained herein is subject to change without notice.

You can purchase VSCOM's products easily from a wide variety of leading technology distributors or partners. Please contact us to find the best ordering method for your needs.

Connect to Success